

SPLASH

IP54 WEATHERPROOF LED DOWNLIGHT

15W

30W

DESCRIPTION

Trim: Die-cast Aluminium (white standard)
Body: Die-cast Aluminium (white standard)
Safety Cover: Clear Glass
Reflector: Pure Anodised Aluminium 99.98%
Weight: 0.29kg (15W), 0.51kg (30W)
Cutout: Ø83mm (15W), Ø114mm (30W)

FEATURES

- 5-year Electrical System Warranty
- High Colour Consistency (MacAdam 3 SDCM)
- Beam angles 25°, 36°, 60°
- Colour temperature 2700K, 3000K, 4000K
- Passive Cooling
- Dimmable
- Low glare 35° cutoff
- CRI >82
- IP54



CE

ø83mm (15W)
ø114mm (30W)



ø95mm (15W)
ø123mm (30W)

52mm (15W)
64mm (30W)

ORDERING CODE ¹	DESCRIPTION	POWER WATTAGE	LUMEN OUTPUT
112920-XX-YY	SPLASH IP54 15W LED DOWNLIGHT 3000K 25°	15	1100
112921-XX-YY	SPLASH IP54 15W LED DOWNLIGHT 3000K 36°	15	1100
112922-XX-YY	SPLASH IP54 15W LED DOWNLIGHT 3000K 60°	15	1100
112923-XX-YY	SPLASH IP54 15W LED DOWNLIGHT 4000K 25°	15	1100
112924-XX-YY	SPLASH IP54 15W LED DOWNLIGHT 4000K 36°	15	1100
112925-XX-YY	SPLASH IP54 15W LED DOWNLIGHT 4000K 60°	15	1100
112926-XX-YY	SPLASH IP54 30W LED DOWNLIGHT 3000K 25°	30	2200
112927-XX-YY	SPLASH IP54 30W LED DOWNLIGHT 3000K 36°	30	2200
112928-XX-YY	SPLASH IP54 30W LED DOWNLIGHT 3000K 60°	30	2200
112929-XX-YY	SPLASH IP54 30W LED DOWNLIGHT 4000K 25°	30	2200
112930-XX-YY	SPLASH IP54 30W LED DOWNLIGHT 4000K 36°	30	2200
112931-XX-YY	SPLASH IP54 30W LED DOWNLIGHT 4000K 60°	30	2200

¹ Ordering codes:
 XX = CRI (refer to table)
 YY = Control Options (PD = Phase Dim, ND = Non-Dim, DA = DALI)

Specifications subject to change without notice. Updated 31 Aug 2016.